




Na všechny strany výkyvné o 30°.
Žádná těsnění podléhající opotřebení. Dlouhý bezproblémový provoz i při častém přestavování.

P_{max} : 25 bar



Pro sérii	Objednací číslo				Rozměry [mm]										Hmotnost (mosaz)	
	typ	číslo materiálu			kód	D ₁	D ₂	G ₁	G ₂	L _{G1}	L _{G2}	L	SW ₁	SW ₂		SW ₃
		16	16	30												
422/460/544/612 632/686/688	092.020	-	○	○	AD	-	-	G ¹ / ₄	G ¹ / ₄	12,0	11,5	60,3	27	27	17	60 g
	092.021	-	○	○	AF	-	-	G ³ / ₈	G ¹ / ₄	12,0	11,5	58,3	27	27	17	80 g
	092.030	-	○	○	AF	-	-	G ³ / ₈	G ³ / ₈	12,0	12,0	56,7	27	30	19	80 g
422/460/544/612 632/686/688	092.020	○	-	-	SD	20,0	15,0	-	G ¹ / ₄	-	11,5	64,3	-	27	17	60 g
	092.030	○	-	-	SF	22,0	15,0	-	G ³ / ₈	-	12,0	58,7	-	30	19	80 g
216/302/468/652/679/684	092.022	-	○	○	AD	-	-	G ¹ / ₄	G ³ / ₈ A ISO 228	12,0	10,0	63,8	27	27	17	80 g
	092.022	-	○	○	AF	-	-	G ³ / ₈	G ³ / ₈ A ISO 228	12,0	10,0	61,8	27	27	17	85 g
216/302/468/652/679/684	092.022	○	-	-	SE	20,0	15,0	-	G ³ / ₈ A ISO 228	-	10,0	67,8	-	27	17	80 g

Příklad objednání: typ + číslo materiálu + kód = objednací číslo
092.020 + 16 + AD = 092.020. 16. AD