



Tongue-type nozzles Series 688/689





**Hard, sharp flat fan,
narrowly delimited jet
pattern. Not prone to
clogging.**

Applications:

Cleaning, washing,
degreasing and phosphating,
preparation techniques.



Spray angle 	η	Ordering no.					B \varnothing [mm]	\dot{V} [l/min]				Dimensions		Weight	Spray width B at p=2 bar 	
		Type	Mat. no.		Code G			p [bar]				L [mm]	Hex [mm]		H = 250 mm	H = 500 mm
			16 303 SS	5E PVDF	- 3/8 BSPT	- 3/4 BSPP		0.5	1.0	2.0	5.0					
45°	35°	688.763	○	-	CE	-	3.0	4.00	5.66	8.00	12.65	43	19	114 g	220	440
	30°	688.843	○	-	CE	-	3.8	6.25	8.84	12.50	19.76	50	19	133 g	220	440
	29°	688.923	○	-	CE	-	4.8	10.00	14.14	20.00	31.62	59	22	247 g	220	440
	35°	689.003	○	○	-	90	6.0	15.75	22.27	31.50	49.81	80/80	32/24	306/33	250	490

B = bore diameter

Example **Type** + **Material-no.** + **Code** = **Ordering no.**
for ordering: **688.763** + **16** + **CE** = **688.763.16.CE**

The folded page at the end of the catalogue will give you a survey on the various assembly possibilities. For complete assembly accessories, please refer to "Accessories".



Phosphating line