







Accessories Ball joints

Allround swivelling action of 30°.
No sealings, no wear.
Long service life even after many adjustments.
P_{max}: 25 bar.



For Series	Ordering no.				Dimensions [mm]											Weight (Brass)
	Type	Material no.			Code	D ₁	D ₂	G ₁ BSPP	G ₂ BSPP	L _{G1}	L _{G2}	L	Hex ₁	Hex ₂	Hex ₃	
		16 303 SS/ 316Ti SS	16 303 SS	30 Brass												
For all nozzles with 1/4 male thread.	092.020	-	○	○	AD	-	-	1/4	1/4	12.0	11.5	60.3	27	27	17	190 g
	092.021	-	○	○	AF	-	-	3/8	1/4	12.0	11.5	58.3	27	27	17	170 g
For all nozzles with 3/8 male thread.	092.030	-	○	○	AF	-	-	3/8	3/8	12.0	12.0	56.7	27	30	19	160 g
For all nozzles with 1/4 male thread.	092.020	○	-	-	SD	20.0	15.0	-	1/4	-	11.5	64.3	-	27	17	150 g
	092.030	○	-	-	SF	22.0	15.0	-	3/8	-	12.0	58.7	-	30	19	150 g
226/2TR/216/302/308/350 548/468/679/684/652	092.022	-	○	○	AD	-	-	1/4	3/8	12.0	10.0	63.8	27	27	17	135 g
	092.022	-	○	○	AF	-	-	3/8	3/8	12.0	10.0	61.8	27	27	17	165 g
226/2TR/216/302/308/350 548/468/679/684/652	092.022	○	-	-	SE	20.0	15.0	-	3/8	-	10.0	67.8	-	27	17	155 g

Compact ball joints for narrow installation conditions



For all nozzles with 1/8 male thread	092.010	-	○	○	AA	-	-	1/8	1/8	8.0	8.0	29.3	22	24	-	70 g
For all nozzles with 1/4 male thread	092.024	-	○	○	AC	-	-	1/4	1/4	12.0	12.0	44	27	27	-	140 g
For all nozzles with 3/8 male thread	092.030	-	○	○	AE	-	-	3/8	3/8	12.0	12.0	44	27	30	-	160 g