

For type 01



Spacing rings made from anodised aluminium or polymer (POM)



Aluminium



Plastic





PRT with mounted spacing ring

Dimensions [mm]

D	D1	T2	S2	D3	h1	Part No. ³⁹⁾
80	70	6 x 60°	4.5	62	10	PRT-01-20-DR
100	91	8 x 45°	4.5	84	11	PRT-01-30-DR
150	135	16 x 22.5°	6.6	122	13	PRT-01-50-DR
160	145	20 x 18°	5.5	132	13	PRT-01-60-DR
185	170	16 x 22.5°	5.5	162	13	PRT-01-100-DR
250	235	16 x 22.5°	5.5	222	13	PRT-01-150-DR
300	285	16 x 22.5°	7.0	276	13	PRT-01-200-DR
450	430	16 x 22.5°	9.0	412	15	PRT-01-300-DR

³⁹⁾ Please add suffix "-POM" for plastic version (not available for sizes 150 and 300)

Spacing ring for heavy duty applications **New**



- Steel version to avoid distortion during installation
- Dimensional range of 20mm to 300mm inner diameters
- iglidur® PRT modular system: can be combined with all sizes
- High corrosion resistance
- Lubrication and maintenance-free

Dimensions [mm]

D	D1	T2	S2	D3 ±0.2	h1	Part No.
80	70	6 x 60°	4.5	62	20	PRT-01-20-DR-HD
100	91	8 x 45°	4.5	84	22	PRT-01-30-DR-HD
150	135	16 x 22.5°	6.6	122	26	PRT-01-50-DR-HD
160	145	20 x 18°	5.5	132	26	PRT-01-60-DR-HD
185	170	16 x 22.5°	5.5	162	26	PRT-01-100-DR-HD
250	235	16 x 22.5°	5.5	222	26	PRT-01-150-DR-HD
300	285	16 x 22.5°	7.0	276	26	PRT-01-200-DR-HD
450	430	16 x 22.5°	9.0	412	30	PRT-01-300-DR-HD