



Image exemplary

- 5,000,000**
Double strokes guaranteed
- 15 x d**
Bend radius, e-chain®
- 10m**
Travel distance, e-chain®

- For flexing applications
- PVC outer jacket
- Shielded
- Flame-retardant

Dynamic information

	Bend radius	e-chain® linear flexible	minimum 15 x d minimum 12 x d
	Temperature	e-chain® linear flexible	+5°C up to +70°C -5°C up to +70°C (following DIN EN 60811-504) -15°C up to +70°C (following DIN EN 50305)
	v max.	unsupported	3m/s
	a max.		20m/s²
	Travel distance		Unsupported travels up to 10m, Class 1

Cable structure

	Conductor	Conductor consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality, especially low-capacitance TPE mixture.
	Core structure	Power cores and control pair elements wound together in an optimised pitch length.
	Core identification	Power cores: Black cores with white numbers, one green-yellow core. 1. Core: U / L1 / C / L+ 2. Core: V / L2 3. Core: W / L3 / D / L- 1 control pair: Black cores with white numbers. 1. Control core: 5 2. Control core: 6 2 control pairs: Black cores with white numbers. 1. Control core: 5 2. Control core: 6 3. Control core: 7 4. Control core: 8 Foil taping of optimised, bending-resistant foil shield.
	Element shield	
	Overall shield	Braiding made of tinned copper wires. Coverage approx. 60% optical
	Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains®. Colour: Pastel orange (similar to RAL 2003)

Electrical information

	Nominal voltage	600/1,000V (following DIN VDE 0298-3) 1,000V (following UL)
	Testing voltage	4,000V (following DIN EN 50395)

Class 3.1.1.1

Properties and approvals

	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	PTFE-free	The design of these products does not contain PTFE
	UL-verified	Certificate No. V293650: „igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	UL/CSA AWM	See data sheet for details ► www.igus.sk/CF887
	NFFA	Following NFPA 79-2018, chapter 12.9
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	CE	Following 2014/35/EU

Guaranteed service life (details see page 14-15)

Double strokes*	1 million	3 million	5 million
Temperature, from/to [°C]	R min. [x d]	R min. [x d]	R min. [x d]
+5/+15	17.5	18.5	19.5
+15/+60	15	16	17
+60/+70	17.5	18.5	19.5

* Higher number of double strokes? Service life calculation online ► www.igus.sk/chainflexlife

Typical application areas

- For flexing applications, Class 3
- Especially for unsupported travels, Class 1
- Without influence of oil, Class 1
- No torsion, Class 1
- Preferably indoor applications
- Wood/stone processing, packaging industry, feeding, handling, adjusting devices

Part No.	Number of cores and conductor nominal cross section [mm ²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]	Shop and prices online 
1 control pair shielded					
CF887.07.05.02.01	(4G0.75+(2x0.5)C)C	10.0	69	119	www.igus.sk CF887
CF887.15.15.02.01	(4G1.5+(2x1.5)C)C	12.5	124	200	
CF887.25.15.02.01	(4G2.5+(2x1.5)C)C	13.5	182	254	
CF887.40.15.02.01	(4G4.0+(2x1.5)C)C	14.5	236	340	
2 control pairs shielded					
CF887.10.07.02.02	(4G1.0+2x(2x0.75)C)C	11.5	110	184	www.igus.sk CF887
CF887.15.15.02.02	(4G1.5+2x(2x1.5)C)C	13.5	164	253	
CF887.25.15.02.02	(4G2.5+2x(2x1.5)C)C	14.5	217	325	

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

