

chainflex® CFCLEAN1



- 20 million**
Double strokes guaranteed
- Min. 40mm**
Bend radius e-skin® flat
- 3m**
Travel distance, e-skin® flat

- For heaviest duty applications in e-skin® flat
- PTFE foil wrap
- Shielded
- Highly abrasion-resistant
- PVC-free

Dynamic information

	Bend radius	e-skin® flat linear	minimum 40mm (further radii in preparation, please see data sheet)
		fixed	minimum 3 x d
	Temperature	e-skin® linear	-10°C up to +80°C
		fixed	-25°C up to +90°C (following DIN EN 50305)
	v max.	unsupported	2m/s
	a max.		40m/s ²
	Travel distance		Short, very fast applications with small radii and restricted installation space in an e-skin® flat

Cable structure

	Conductor	Very finely stranded special conductors with especially soft and bending resistant design, made of bare copper wires.
	Core insulation	Mechanically high-quality FEP mixture.
	Core structure	Cores wound in a layer with especially short pitch length.
	Core identification	Cores < 0.5mm²: Colour code in accordance with DIN 47100. Cores ≥ 0.5mm²: White cores with black numbers, one green-yellow core.
	Overall shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer film	Low-adhesion, extremely abrasion-resistant and highly flexible PTFE wrap, adapted to suit the requirements in e-skin® flat. Colour: White

Electrical information

	Nominal voltage	300/300V 300V (following UL)
	Testing voltage	2,000V

Properties and approvals

	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	UL-verified	Certificate No. V293650: „igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	UL AWM	See data sheet for details ► www.igus.eu/CFCLEAN1
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	Air Purity Class 1, material/stranded structure tested by IPA according to ISO 14644-14, test report IG 2107-1242
	CE	Following 2014/35/EU

Typical application areas

- For heaviest duty applications and especially small radii in cleanroom with e-skin® flat
- Especially for short, very fast applications with small radii and restricted installation space
- Indoor applications with e-skin® flat
- Semi-conductor/OLED manufacturing, medical cleanroom



chainflex® CFCLEAN are not cables in the sense of the normal standards for cables. Due to the absence of the outer jacket in CFCLEAN, which provides mechanical protection for cables, the use of chainflex® CFCLEAN is only permitted inside e-skin® flat.

Part No.	Number of cores and conductor nominal cross section [mm ²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]	Shop and prices online
CFCLEAN1.02.04	(4x0.25)C	3.5	21	27	
CFCLEAN1.03.02	(2x0.34)C	3.5	17	22	
CFCLEAN1.03.07	(7x0.34)C	5.0	40	50	
CFCLEAN1.05.04	(4G0.5)C	5.0	36	49	
CFCLEAN1.07.04	(4G0.75)C	5.0	50	63	
CFCLEAN1.07.05	(5G0.75)C	5.5	58	74	
CFCLEAN1.10.02	(2x1.0)C	5.0	37	49	

www.igus.eu/CFCLEAN1

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



HENNLICH s.r.o. - LIN-TECH
Košťany nad Turcom 543,
038 41 Košťany nad Turcom

Telefón: +421 940 982 865
E-mail: litech@hennlich.sk

www.hennlich.sk/lin-tech



HENNLICH s.r.o. - LIN-TECH
Košťany nad Turcom 543,
038 41 Košťany nad Turcom

Telefón: +421 940 982 865
E-mail: litech@hennlich.sk

UL-verified chainflex® guarantee ... www.igus.sk/ul-verified