



**20 million**  
Double strokes guaranteed



**Min. 40mm**  
Bend radius e-skin® flat



**3m**  
Travel distance, e-skin® flat

- For heaviest duty applications in e-skin® flat
- PTFE foil wrap
- Shielded
- Highly abrasion-resistant
- PVC-free

### Dynamic information

	<b>Bend radius</b>	<b>e-skin® flat linear</b>	minimum 40mm (further radii in preparation, please see data sheet)
		<b>fixed</b>	minimum 3 x d
	<b>Temperature</b>	<b>e-skin® linear</b>	-10°C up to +80°C
		<b>fixed</b>	-25°C up to +90°C (following DIN EN 50305)
	<b>v max.</b>	<b>unsupported</b>	2m/s
	<b>a max.</b>		40m/s <sup>2</sup>
	<b>Travel distance</b>		Short, very fast applications with small radii and restricted installation space in an e-skin® flat

### Cable structure

	<b>Conductor</b>	Very finely stranded special conductors with especially soft and bending resistant design, made of bare copper wires.
	<b>Core insulation</b>	Mechanically high-quality PTFE mixture.
	<b>Core structure</b>	Cores wound in a layer with especially short pitch length.
	<b>Core identification</b>	White core with black imprint ► <a href="#">Product range table</a>
	<b>Element shield</b>	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	<b>Outer film</b>	Low-adhesion, extremely abrasion-resistant and highly flexible PTFE wrap, adapted to suit the requirements in e-skin® flat. Colour: White

### Electrical information

	<b>Nominal voltage</b>	300/300V
	<b>Testing voltage</b>	2,000V

### Properties and approvals

	<b>Silicone-free</b>	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	<b>UL-verified</b>	Certificate No. V293650: „igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	<b>REACH</b>	In accordance with regulation (EC) No. 1907/2006 (REACH)
	<b>Lead-free</b>	Following 2011/65/EC (RoHS-II/RoHS-III)
	<b>Cleanroom</b>	Air Purity Class 1, material/stranded structure tested by IPA according to ISO 14644-14, test report IG 2107-1242
	<b>CE</b>	Following 2014/35/EU

### Typical application areas

- For heaviest duty applications and especially small radii in cleanroom with e-skin® flat
- Especially for short, very fast applications with small radii and restricted installation space
- Indoor applications with e-skin® flat
- Semi-conductor/OLED manufacturing, medical cleanroom





chainflex® CFCLEAN are not cables in the sense of the normal standards for cables. Due to the absence of the outer jacket in CFCLEAN, which provides mechanical protection for cables, the use of chainflex® CFCLEAN is only permitted inside e-skin® flat.

Part No.	Number of cores and conductor nominal cross section [mm <sup>2</sup> ]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]	Shop and prices online
CFCLEAN2.KOAX1.03	3xHF75-0.3/1.6	6.5	23	57	<a href="http://www.igus.eu/CFCLEAN2">www.igus.eu/CFCLEAN2</a>

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.  
G = with green-yellow earth core x = without earth core

Part No.	Characteristic wave impedance approx. [Ω]	Core identification
CFCLEAN2.KOAX1.03	75	Coax 75Ohm -1-, Coax 75Ohm -2-, Coax 75Ohm -3-



**HENNLICH s.r.o. - LIN-TECH**  
Košťany nad Turcom 543,  
038 41 Košťany nad Turcom

Telefón: +421 940 982 865  
E-mail: [lintech@hennlich.sk](mailto:lintech@hennlich.sk)

[www.hennlich.sk/lin-tech](http://www.hennlich.sk/lin-tech)



**HENNLICH s.r.o. - LIN-TECH**  
Košťany nad Turcom 543,  
038 41 Košťany nad Turcom

Telefón: +421 940 982 865  
E-mail: [lintech@hennlich.sk](mailto:lintech@hennlich.sk)

4-year guarantee ... more than 1,350 cable types from stock ... no cutting costs

UL-verified chainflex® guarantee ... [www.igus.sk/ul-verified](http://www.igus.sk/ul-verified)