

chainflex® CFCLEAN4



20 million
Double strokes guaranteed



Min. 40mm
Bend radius e-skin® flat



3m
Travel distance, e-skin® flat

- For heaviest duty applications in e-skin® flat
- PTFE foil wrap
- Shielded
- Highly abrasion-resistant
- PVC-free

Dynamic information

	Bend radius	e-skin® flat linear	minimum 40mm (further radii in preparation, please see data sheet)
		fixed	minimum 3 x d
	Temperature	e-skin® linear	-10°C up to +80°C
		fixed	-25°C up to +90°C (following DIN EN 50305)
	v max.	unsupported	2m/s
	a max.		40m/s ²
	Travel distance		Short, very fast applications with small radii and restricted installation space in an e-skin® flat

Cable structure

	Conductor	Very finely stranded special conductors with especially soft and bending resistant design, made of bare copper wires.
	Core insulation	Mechanically high-quality FEP mixture.
	Core structure	According to measuring system specification.
	Core identification	According to measuring system specification.
	Overall shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer film	Low-adhesion, extremely abrasion-resistant and highly flexible PTFE wrap, adapted to suit the requirements in e-skin® flat. Colour: White

Electrical information

	Nominal voltage	300/300V 300V (following UL)
	Testing voltage	2,000V

Properties and approvals

	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	UL-verified	Certificate No. V293650: „igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“ See data sheet for details ► www.igus.eu/CFCLEAN4
	UL AWM	
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	Air Purity Class 1, material/stranded structure tested by IPA according to ISO 14644-14, test report IG 2107-1242
	CE	Following 2014/35/EU

Typical application areas

- For heaviest duty applications and especially small radii in cleanroom with e-skin® flat
- Especially for short, very fast applications with small radii and restricted installation space
- Indoor applications with e-skin® flat
- Semi-conductor/OLED manufacturing, medical cleanroom





chainflex® CFCLEAN are not cables in the sense of the normal standards for cables. Due to the absence of the outer jacket in CFCLEAN, which provides mechanical protection for cables, the use of chainflex® CFCLEAN is only permitted inside e-skin® flat.

Part No.	Number of cores and conductor nominal cross section [mm ²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]	Shop and prices online
CFCLEAN4.015	(4x(2x0.14)+4x0.5)C	6.5	60	77	

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Part No.	Core group	Colour code
CFCLEAN4.015	4x(2x0.14)	brown/green, yellow/violet, grey/pink, red/black
	4x0.5	blue, white, brown-green, white-green



igus® chainflex® CFCLEAN4

HENNLICH s.r.o. - LIN-TECH
Košťany nad Turcom 543,
038 41 Košťany nad Turcom

Telefón: +421 940 982 865
E-mail: litech@hennlich.sk

www.hennlich.sk/lin-tech



HENNLICH s.r.o. - LIN-TECH
Košťany nad Turcom 543,
038 41 Košťany nad Turcom

Telefón: +421 940 982 865
E-mail: litech@hennlich.sk

UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

4-year guarantee ... more than 1,350 cable types from stock ... no cutting costs