

5,000,000
Double strokes guaranteed15 x d
Bend radius, e-chain®10m
Travel distance, e-chain®

- For flexing applications
- PVC outer jacket
- Flame-retardant

Dynamic information

	Bend radius	e-chain® linear	minimum 15 x d
		flexible	minimum 12 x d
		fixed	minimum 8 x d
	Temperature	e-chain® linear	+5°C up to +70°C
		flexible	-5°C up to +70°C (following DIN EN 60811-504)
		fixed	-15°C up to +70°C (following DIN EN 50305)
	v max.	unsupported	3m/s
	a max.		20m/s²
	Travel distance		Unsupported travels up to 10m, Class 1

Cable structure

	Conductor	Conductor consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality, especially low-capacitance TPE mixture.
	Core structure	Cores wound with an optimised pitch length.
	Core identification	Black cores with white numbers, one green-yellow core. 1. Core: U / L1 / C / L+ 2. Core: V / L2 3. Core: W / L3 / D / L-
	Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains®. Colour: Pastel orange (similar to RAL 2003)

Electrical information

	Nominal voltage	600/1,000V (following DIN VDE 0298-3) 1,000V (following UL)
	Testing voltage	4,000V (following DIN EN 50395)

Properties and approvals

	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	PTFE-free	The design of these products does not contain PTFE

Class 3.1.1.1



UL-verified



UL/CSA AWM



NFPA



REACH



Lead-free



CE

Certificate No. V293650: igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year*

See data sheet for details ► www.igus.sk/CF885

Following NFPA 79-2018, chapter 12.9

In accordance with regulation (EC) No. 1907/2006 (REACH)

Following 2011/65/EC (RoHS-II/RoHS-III)

Following 2014/35/EU

Guaranteed service life (details see page 14-15)

Double strokes*	1 million	3 million	5 million
Temperature, from/to [°C]	R min. [x d]	R min. [x d]	R min. [x d]
+5/+15	17.5	18.5	19.5
+15/+60	15	16	17
+60/+70	17.5	18.5	19.5

* Higher number of double strokes? Service life calculation online ► www.igus.sk/chainflexlife

Typical application areas

- For flexing applications, Class 3
- Especially for unsupported travels, Class 1
- Without influence of oil, Class 1
- No torsion, Class 1
- Preferably indoor applications
- Wood/stone processing, packaging industry, feeding, handling, adjusting devices

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]	Shop and prices online
CF885.15.04	4G1.5	8.0	67	105	 www.igus.sk/CF885
CF885.25.04	4G2.5	10.0	110	163	
CF885.40.04	4G4.0	11.5	175	244	
CF885.60.04	4G6.0	13.5	237	360	
CF885.100.04	4G10	17.0	412	514	
CF885.160.04	4G16	20.0	690	857	

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this online: www.igus.sk/cf-case