

Medium voltage cable | PUR outer jacket

chainflex® CFCRANE.PUR



10 million
Double strokes guaranteed



10 x d
Bend radius, e-chain®



400m
Travel distance, e-chain®

- For maximum voltages and outputs
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Flame-retardant
- PVC and halogen-free
- Notch-resistant
- Hydrolysis and microbe-resistant

Dynamic information

	Bend radius	e-chain® linear	minimum 10 x d
		flexible	minimum 8 x d
		fixed	minimum 5 x d
	Temperature	e-chain® linear	-20°C up to +80°C
		flexible	-25°C up to +80°C (following DIN EN 60811-504)
		fixed	-30°C up to +80°C (following DIN EN 50305)
	v max.	unsupported	10m/s
		gliding	6m/s
	a max.		50m/s ²
	Travel distance		Unsupported travels and up to 400m and more for gliding applications, Class 6

Cable structure

	Conductor	Highly-flexible cable consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Inner and outer semiconducting layer made of conductive rubber. Insulating sheath made of highly-quality, heat-resistant and ozone-proof ethylene propylene rubber (EPR).
	Overall shield	Extremely bending-resistant wrapping made of tinned copper wires Coverage approx. 85% optical
	Outer jacket	Low-adhesion, halogen-free, highly abrasion resistant PUR mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-10-2) Colour: Fire red (similar to RAL 3000)

Electrical information

	Nominal voltage	6/10kV or 8.7/15kV (following DIN VDE 0250), further voltages upon request.
	Testing voltage	24kV (following DIN VDE 0250, Part 813)

Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (following DIN EN 50363-10-2), Class 3
	Flame-retardant	According to IEC 60332-1-2
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)

4-year guarantee ... more than 1,350 cable types from stock ... no cutting costs

Phase-out model

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	7	≥ 400m
none	1	2	3	4	5	6	7	highest
none	1	2	3	4	5	6	7	±360°

Class 6.6.3.1



Halogen-free

Following DIN EN 60754



PTFE-free

The design of these products does not contain PTFE



UL-verified

Certificate No. V293650: „igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
In accordance with regulation (EC) No. 1907/2006 (REACH)



REACH



Lead-free

Following 2011/65/EC (RoHS-II/RoHS-III)



CE

Following 2014/35/EU

Guaranteed service life (details see page 14-15)

Double strokes*	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [x d]	R min. [x d]	R min. [x d]
-20/-10	12.5	13.5	14.5
-10/+70	10	11	12
+70/+80	12.5	13.5	14.5

* Higher number of double strokes? Service life calculation online ► www.igus.sk/chainflexlife

Typical application areas

- For maximum voltages and outputs, Class 6
- Unsupported travels and up to 400m and more for gliding applications, Class 6
- Almost unlimited resistance to oil, Class 3
- No torsion, Class 1
- Indoor and outdoor applications, UV-resistant
- Ship to shore, crane applications, conveyor technology

Part No.	Number of cores and conductor nominal cross section [mm ²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]	Shop and prices online
CFCRANE.PUR.350.01.6/10kV ¹⁾	(1x35/16)C	26.0	568	852	 www.igus.sk/CFCRANEPUR
CFCRANE.PUR.500.01.6/10kV ¹⁾	(1x50/16)C	27.0	722	1025	
CFCRANE.PUR.700.01.6/10kV ¹⁾	(1x70/16)C	29.0	941	1249	
CFCRANE.PUR.950.01.6/10kV ¹⁾	(1x95/16)C	31.0	1166	1523	

¹⁾ Phase-out model

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.

G = with green-yellow earth core x = without earth core



igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year

UL-verified chainflex® guarantee ... www.igus.sk/ul-verified