#### Lubrication

Grease Gun Unit MG70

# **Lubrication Equipment**

## **Grease Gun Unit MG70**

Discharge pressure: 19.6 MPa max Discharge rate: 0.6 cm³/stroke DGrease: 70 g/80 g bellows cartridge
Overall length: 235 mm (excluding the nozzle) DWeight: 480 g (including the nozzle, excluding the grease)



The MG70 grease gun unit is designed especially for use with 70 g and 80 g bellows cartridges. It allows the user to grease the insides of products without dirtying their hands.

The grease gun features a slit window, allowing the user to check the remaining amount of grease.

#### [How to Lubricate]

- (1) Depending on the product that you wish to grease, attach either the Type H or dedicated Type U nozzle to the grease gun unit. You can then also install one of the tip attachments (Type N, Type P, or Type L) to the Type U nozzle.
- (2) Push the tip of the grease gun into the grease nipple and apply the grease in a way that ensures it does not protrude out from the side.

#### [Supported Model Numbers]

Unit: mm

| Туре                          | Dimensions                           | Supported model numbers |   |  |
|-------------------------------|--------------------------------------|-------------------------|---|--|
| Type N                        | Ø6 25<br>M5×0.5                      | LM Guide                | Models SSR15, SHS15, SR15, HSR12,<br>HSR15, CSR15, HRW17, GSR15, SRS15G,<br>RSR15M1, HCR12, and HCR15 |  |
|                               |                                      | Cam Follower<br>Rod End | Models CF, CFN-A, and CF-SFU Models PHS5 to 22 and POS8 to 22   |  |
| Type P                        | ø6 ø1.8 25<br>M5×0.5                 | LM Guide                | Models HSR8, HSR10, HRW12, HRW14, and RSR12M1   |  |
|                               |                                      | Cam Follower            | Models CF-AB, CFH-AB, and NUCF-AB   |  |
| Type L                        | 6 3 Ø 6 M5×0.5                       | LM Guide                | Models HSR8, HSR10, HRW12, HRW14,<br>and RSR12M1  |  |
| Type H                        | 120<br>30 81<br>Ø 10<br>R1/8 (PT1/8) | LM Guide                | Models with grease nipple M6F or PT1/8  |  |
|                               |                                      | Ball Screw              |   |  |
|                               |                                      | Rod End                 | Models PHS25, PHS30, POS25, and POS30   |  |
| Dedicated<br>Type U<br>nozzle | 181<br>161 11<br>Ø6                  | _                       | _   |  |


Note) Types P and L are also capable of greasing less accessible areas for model numbers other than those listed above (by dripping grease on the raceway).

#### Model number coding

### MG70

Dedicated grease gun for 70 g and 80 g grease bellows cartridges

In addition to the grease gun unit, this also comes with a dedicated Type U nozzle, dedicated attachments (Type N, Type P, and Type L) and the Type H. \*Please contact THK regarding grease guns that use 400 g cartridges.







Tel.: 0940 644 565 E-mail: lintech@hennlich.sk