





e-chains® | Series 06 | One-piece, non-openable


Part No. e-chains®	Bi [mm]	Ba [mm]	R Available bend radii [mm]			Weight [kg/m]
06.06.R.0	6	12.5	018	028	038	≈ 0.13
06.10.R.0	10	16.5	018	028	038	≈ 0.14
06.16.R.0	16	22.5	018	028	038	≈ 0.16
06.20.R.0	20	27	018	028	038	≈ 0.17
06.30.R.0	30	37	018	028	038	≈ 0.20
06.40.R.0	40	47	018	028	038	≈ 0.23
06.50.R.0	50	57	018	028	038	≈ 0.26
06.64.R.0	64	71	018	028	038	≈ 0.30

Complete Part No. with required radius (R). Example: 06.10.028.0

Installation dimensions




Inner height [mm]	10.5
Pitch [mm/link]	20
Links/m	50
corresponds to [mm]	1,000
e-chain® length	$L_K = S/2 + K$



R	018	028	038
H	51	71	91
D	56	66	76
K	100	130	160


The required clearance height: $H_F = H + 10\text{mm}$ (with 0.2kg/m fill weight)290 More information ► www.igus.eu/06

igus



Width index	Part No. full set with tie-wrap plates	Part No. full set without tie-wrap plates	A [mm]	B [mm]	Number of teeth
06. ►	060.06.12PZ	060.06.12	—	12.5	1
10. ►	060.10.12PZ	060.10.12	—	16.5	1
16. ►	060.16.12PZ	060.16.12	—	22.5	2
20. ►	060.20.12PZ	060.20.12	—	27.0	2
30. ►	060.30.12PZ	060.30.12	22	37.0	3
40. ►	060.40.12PZ	060.40.12	32	47.0	4
50. ►	060.50.12PZ	060.50.12	42	57.0	5
64. ►	060.64.12PZ	060.64.12	56	71.0	6

Material mounting bracket - igumid G, temperature: -40° up to +120°C, VDE 0304 IIC UL94-HB



Possible variations for assembled mounting brackets. To receive brackets pre-fitted please add index .A1, .A2, .A3 or .A4.

060.10.12PZ.A1 Order example

.A... to indicate option with brackets pre-fitted

With integrated strain relief tie-wrap plates

Full set

Series

igus 3D CAD, service life calculation, configurators and more ► www.igus.eu/E2micro

291